VOLVO

Volvo Buses. Driving quality of life

VOLVO B8R SUNSUNDEGUI SB3

Versatile, reliable, fuel efficient, a coach for all seasons



Model Volvo B8R 2-axle coach

Body specification Sunsundegui SB3

Engine Volvo D8K 320 6cyl 7.7 litre Euro 6 engine rated at 320hp @2100 rpm with maximum torque of 1200Nm

at 1100-1500rpm. Optional 350hp engine available with 1400Nm maximum torque at 1200-1600rpm.

Engine emission control uses SCR, EGR, DPF & DOC technology.

Transmission ZF Ecolife 6AP1400C 6 speed automatic hydraulic transmission.

Dimensions Height 3.3 m Width 2.55 m Length 12.25 m

Fuel tank 300 litres

Technical standard European National Small Series Type Approval (NSSTA)

Body construction Under frame 3CR12 stainless steel. Rest of frame in standard steel.

Safety features EBS (Electronic Braking System) featuring ABS and ASR functions (Antilock and Antislip). ESP (Electronic

Stability Programme). Driver support system including Collision Warning Emergency Braking system

(CWEB), Lane Keeping Support system (LKS).

Driver's seatPneumatic driver's seat ISRI 6860/875 NTS with three point seat belt, headrests and 1 arm rest.

Passenger seats 72 seats in 3+2 configuration with three point seat belts and headrests covered in leather imitation.

Luggage capacity 5,18 m³ approx (not including internal luggage racks).

Glazing Laminated Opticool windscreen with dual speed windscreen wipers. Electrical side windows and

individually operated driver and guide sun blinds. Double tinted side windows with curtains to all

passenger windows (optional).

Air conditioning Roof mounted EBERSPACHER (Carrier Sutrak) AC 353 Gen 4 Type I unit with automatic control. 24kW

cooling capacity and 38kW heating capacity.

Audio/Visual Bosch Classic Line audio systems, Wi-fi (optional), CCTV System with 6 cameras (optional)

Additional features Electric front entrance door, manual rear emergency exit door, tip-up front bumper, acoustic and thermal

insulation, separate heating and ventilation system for driver and guide, heating system by convectors, halogen headlight, fog light and day running lights, internal LED indirect lighting, individual lights LED, Alcoa Dura-Bright alloys (optional), carpets to gangways and all entrances (optional), two electrical demisting rear-view mirrors, air horns, side position lights and high level stop and indicator lights at rear

(LED). Luggage racks (optional)

